

## Data Request Sheet for Doors TT1.1 and TT1.2

Project: \_\_\_\_\_

Customer: \_\_\_\_\_ Customer no.: \_\_\_\_\_

Person in charge: \_\_\_\_\_ Phone: \_\_\_\_\_ E-mail: \_\_\_\_\_

☐ Offer Offer no.: \_\_\_\_\_ Unit price \_\_\_\_\_ €,

☐ Order Order no.: \_\_\_\_\_ Internal base price per unit \_\_\_\_\_ €, Item: \_\_\_\_\_, **P** \_\_\_\_\_

Below you will find our door questionnaire (consisting of four sheets) for the above property. We kindly ask you to fill in the door questionnaire **completely**, confirm the information under point 14 with your signature and return it to us. We would like to point out that the information you provide is a binding part of the contract for the manufacture of the door. The delivery time stated by us begins after the **fully completed** door questionnaire has been returned. **Requested special equipment that is not included in the offer price will only be carried out against payment.**

### 1. Number of leaves:

☐ Single-leaved door TT1.1

☐ Double-leaved door TT1.2


### 2. Material:

☐ 1.4307 (AISI 304 L)

☐ 1.4404 (AISI 316 L)

### 3. Shell dimensions:

(Drawing 1)



Clear width B = \_\_\_\_\_ mm




Clear wall opening F = \_\_\_\_\_ mm

Clear height H = \_\_\_\_\_ mm




**(Please note point 4. sill closure!)**

**4. Sill closure:**

**4.1 Standard sill closure:**


<input type="checkbox"/> step flashing / wall clamps (Drawing 3 b)   (BA1)	<input type="checkbox"/> step flashing / bolted with dowels (Drawing 3 g)   (BA2)
<input type="checkbox"/> non-standard sill, U-profile, sill height: ..... mm (minimal 20mm) (Drawing 3h)   (BA6)	

**4.2 Special sill closure (surcharge):**


<input type="checkbox"/> without step flashing, bolted with dowels (Drawing 3 f)   (BA3)	<input type="checkbox"/> circumferential block frame on four sides (Drawing 3i)   (BA4)
<input type="checkbox"/> circumferential Z-frame on four sides, only RC3 (Drawing 3j)   (BA5)	

**5. Installation situation:**

- ☐ Installation into the lintel  
(Z-frame and block frame possible)  
(Drawing 2 a)




- ☐ Installation into ceiling-high clearance  
(Only block frame possible!)  
(Drawing. 2 b)




**6. Door opening options:**

Single-leaved TT1.1

- ☐ hinges on left  
(Drawing 5 a)




- ☐ hinges on right  
(Drawing 5 b)




Double-leaved TT1.2 – position of hinges on swing leaf  
(as of 135cm the door leaf is divided)

- ☐ hinges on left  
(Drawing 5 c)



- ☐ hinges on right  
(Drawing 5 d)



**Swing leaf**


\_\_\_\_\_ cm  
(min. 40 cm / max. 133 cm)

**Fixable leaf**


\_\_\_\_\_ cm  
(min 30 cm / max. 133 cm)

## 7. Frame and mounting options:


- I.) ☐ Block frame bolted with dowelling clips  
(Drawing 4 b)




- II.) ☐ Block frame bolted through the frame, minimum edge distance 80 mm  
(Drawing 4 c)



- III.) ☐ Z-frame bolted with dowelling clips  
(Drawing 4 e)



- IV.) ☐ Z-frame bolted through the frame  
(Drawing 4 f)



## 8. Door with rigidly mounted louvre on the outside and fly grid on the inside

Size: 1 pc. W x H = 40 x 20 cm

1 pc. W x H = 50 x 30 cm

Installation position: in the upper section

- |                          |                                  |                          |
|--------------------------|----------------------------------|--------------------------|
| <input type="checkbox"/> | inside fly grid only             | <input type="checkbox"/> |
| <input type="checkbox"/> | inside fly grid + movable louvre | <input type="checkbox"/> |
| <input type="checkbox"/> | in the lower section             | <input type="checkbox"/> |

Double door: in the swing leaf ☐

In the fixable leaf ☐

in both leaves ☐

## 9. Installation:

☐ by costumer

☐ by HUBER SE

**10. Optional equipment:**

- |  |   |   |
|--|---|---|
| <input type="checkbox"/> Upper door closer GEZE TS 5000 (door stopper required)  | <input type="checkbox"/> swing leaf $\geq 750$ mm width | <input type="checkbox"/> fixable leaf $\geq 750$ mm width |
| <input type="checkbox"/> Upper door stop manually releasable   | <input type="checkbox"/> swing leaf $\geq 750$ mm width | <input type="checkbox"/> fixable leaf $\geq 750$ mm width |
| <input type="checkbox"/> Lowerable floor seal  |   |   |
| <input type="checkbox"/> One-piece door arrestor (mounted to the door panel), 120 mm lift  | <input type="checkbox"/> swing leaf                     | <input type="checkbox"/> fixable leaf                     |
| <input type="checkbox"/> Two-piece door arrestor/stop (supplied loose)   | <input type="checkbox"/> swing leaf                     | <input type="checkbox"/> fixable leaf                     |
| <input type="checkbox"/> Alarm system in door surface  |   |   |
| <input type="checkbox"/> Magnetic contact (door OPEN/SHUT indicator)   | <input type="checkbox"/> swing leaf                     | <input type="checkbox"/> fixable leaf                     |
| <input type="checkbox"/> Lock-bolt contact (door OPEN/SHUT indicator)  |   |   |
| <input type="checkbox"/> Potential equalisation  | <input type="checkbox"/> on top of frame                | <input type="checkbox"/> on frame bottom                  |
| <input type="checkbox"/> Heating cable in door frame (without outside temperature sensor, without controls) (HEIZ)                 | <input type="checkbox"/> in door frame                  | <input type="checkbox"/> in door panel                    |
| <input type="checkbox"/> Block frame insulation  |   |   |
| <input type="checkbox"/> No profile cylinder on the inside, the door panel is continuous (single profile cylinder / half cylinder) |   |   |
| <input type="checkbox"/> Paint RAL colour _____ (RAL....)  | <input type="checkbox"/> outside                        | <input type="checkbox"/> inside                           |
| <input type="checkbox"/> Additional anti-graffiti lacquer (RAL....)  | <input type="checkbox"/> outside                        | <input type="checkbox"/> inside                           |
| <input type="checkbox"/> Standard lock   | <input type="checkbox"/> button outside, handle inside  | <input type="checkbox"/> handles on both sides            |
| <input type="checkbox"/> Panic lock  | <input type="checkbox"/> button outside, handle inside  | <input type="checkbox"/> handles on both sides            |
| <input type="checkbox"/> Lock for two profile cylinders  | <input type="checkbox"/> button outside, handle inside  | <input type="checkbox"/> handles on both sides            |
| <input type="checkbox"/> Stainless steel lock (for water chamber)  | <input type="checkbox"/> button outside, handle inside  | <input type="checkbox"/> handles on both sides            |
| → only one profile cylinder possible! No anti-panic function!  |   |   |
| <input type="checkbox"/> Steel sheet finish  |   |   |
| <input type="checkbox"/> Wood panel, wood type: _____ (HOLZ)   | <input type="checkbox"/> outside                        | <input type="checkbox"/> inside                           |

**Info: In case of sunlight, the operability may be impaired. In these cases, we recommend a steel sheet finish or wood panel. (see special equipment).**

**11. Other accessories:**

**12. Delivery address** (complete with post code and city)

(If the door is supplied directly onto a site, indicate the available unloading times and contact persons on site.)

**13. Customer's confirmation:**

Customer's representative: \_\_\_\_\_ Date: \_\_\_\_\_ Signature: \_\_\_\_\_

**14. Please return this form to:**

HUBER contact person: \_\_\_\_\_ Phone. Nr. +498462/201- Fax. Nr. +498462/201-399

E-Mail: \_\_\_\_\_@huber.de

**15. Enclosures for the design engineers:**

- ☐ Drawing ☐ Photo ☐ .....